

Ordering Information:

2643S**V*00
12

Material:

Insulator: Polyester, UL94V-0 PBT
Contact: Phosphor Bronze

RoHS COMPLIANT

1. No. of circuits (06~80)

2. Contact Plating
T= Tin plated 120μ” min over 30μ” min. nickel overall
U= Gold flash over 30μ” min. nickel overall
J= 15μ” min. Selective gold on contact area over 30μ” min. nickel overall,
Tin plated on solder or other area
K= 30μ” min. Selective gold on contact area over 30μ” min. nickel overall,
Tin plated on solder or other area

Recommended hole pattern

Circuits	Dim. A	Dim. B	Circuits	Dim. A	Dim. B
6	5.08(.200)	7.62(.300)	44	53.34(2.100)	55.88(2.200)
8	7.62(.300)	10.16(.400)	46	55.88(2.200)	58.42(2.300)
10	10.16(.400)	12.70(.500)	48	58.42(2.300)	60.96(2.400)
12	12.70(.500)	15.24(.600)	50	60.96(2.400)	63.50(2.500)
14	15.24(.600)	17.78(.700)	52	63.50(2.500)	66.04(2.600)
16	17.78(.700)	20.32(.800)	54	66.04(2.600)	68.58(2.700)
18	20.32(.800)	22.86(.900)	56	68.58(2.700)	71.12(2.800)
20	22.86(.900)	25.40(1.000)	58	71.12(2.800)	73.66(2.900)
22	25.40(1.000)	27.94(1.100)	60	73.66(2.900)	76.20(3.000)
24	27.94(1.100)	30.48(1.200)	62	76.20(3.000)	78.74(3.100)
26	30.48(1.200)	33.02(1.300)	64	78.74(3.100)	81.28(3.200)
28	33.02(1.300)	35.56(1.400)	66	81.28(3.200)	83.82(3.300)
30	35.56(1.400)	38.10(1.500)	68	83.82(3.300)	86.36(3.400)
32	38.10(1.500)	40.64(1.600)	70	86.36(3.400)	88.90(3.500)
34	40.64(1.600)	43.18(1.700)	72	88.90(3.500)	91.44(3.600)
36	43.18(1.700)	45.72(1.800)	74	91.44(3.600)	93.98(3.700)
38	45.72(1.800)	48.26(1.900)	76	93.98(3.700)	96.52(3.800)
40	48.26(1.900)	50.80(2.000)	78	96.52(3.800)	99.06(3.900)
42	50.80(2.000)	53.34(2.100)	80	99.06(3.900)	101.60(4.000)

REV.	ECO. NO.	CHG.	APP.	DATE	DESCRIPTION
F	ES101227				
E	ES071009				
D	ES050431				
C	E000222				
A	DWG REL				

LEOCO CORPORATION

GENERAL TOLERANCES:
(UNLESS SPECIFIED)

	mm	inch
1 PLACE	± 0.30	± --
2 PLACES	± 0.20	± .012
3 PLACES	± 0.10	± .008
4 PLACES	± --	± .004

ANGULAR ± (1°)

APPROVED:

DATE:

CHECKED:

DATE:

DRAWN:

DATE:

UNITS
mm
inch

SCALE
2:1

SIZE
A4

SHEET
1/1

REV.
F

PART NO.:
2643S**V*00

TITLE:
HEADER

DRAWING NO.:
264302S